



EMERGENCY SITUATIONS > *Panic Alert* is a **LoadTrak™** feature that enables drivers to notify their company in an emergency situation.

Working alone? Feel safe and secure with Panic Alert.

PANIC ALERT. INTELLIGENT SAFETY & SECURITY.

- The *Panic Alert* remote devices offer drivers increased safety, security and peace of mind.
- The *Panic Alert* devices are small enough to be carried on the driver at all times, so it will never be out of reach if the driver needs help.
- *Panic Alert* gives drivers access to a 24/7 monitoring centre at the push of a button or by choosing the sensor/man-down mode.
- *Panic Alert* is perfect for drivers travelling alone or working in remote locations.
- The *Panic Alert* devices have a 300-metre signal radius from the vehicle and real-time driver location information.
- *Panic Alert* is available either as a stand-alone product or an add-on option to the **LoadTrak** Vehicle Tracking solution.



In an emergency situation, a driver can press a button or in the event that the driver is immobile, an emergency signal will be sent through the **LoadTrak** device in the truck to the SecurTek monitoring centre. The monitoring centre will then contact the driver's company and indicate the precise location of the driver.

Panic Alert Devices

TPASS



PRODUCT DESCRIPTION:

Dimensions: 2"W, 3 1/8" H, 1 1/2" deep

Battery Type: 9 volt Duracell MN 1604 (included)

Weight: 8 oz. with battery

Battery Life (approx.): Sensing Mode: Up to 30 hours
Alarm Mode: 2 – 4 hours

PRODUCT FEATURES:

Intrinsically Safe:

Certified per ANSI/UL-913 for use in Class 1, Div. 1, Group A, B, C and D Hazardous Locations.

CSA Approved:

Certified to CAN/CSA Std. C22.2 No. 157-92.

High Frequency Radio:

902-928 MHz. No FCC License required.

Automatic Motion Sensing / Man-Down

Alarm Activation:

After 30-35 seconds of immobility, a loud audio alarm will sound and an alarm signal will be sent to the SaskTel Monitoring Centre.

Manual Mode Alarm Activation (Panic Button):

A Manual Push Button can be pressed to send an alarm signal to the SecurTek monitoring centre.

Confirmation that TPASS is active:

Visible Flashing LED lights indicates that the TPASS is active.

Low-Battery Alarm:

An alarm will sound when the battery is at 20% capacity (allowing for one hour operation in alarm mode).

Multiple-Users:

Available to allow multiple users to a single vehicle.

Automatic Activation – Tethered Accountability Key (Option):

The TPASS is automatically turned on when the proprietary tethered accountability key is removed.

Key Fob



PRODUCT DESCRIPTION:

Dimensions: 1 9/16"W, 2 3/4"H, 1/2" deep

Battery Type: Two CR2025 Button Cell Batteries

Battery Life (approx.): up to one year

PRODUCT FEATURES:

Manual Mode Alarm Activation (Panic Button):

A Manual Push Button can be pressed to send an alarm signal to the SecurTek monitoring centre.

Low-Battery Alarm:

When the battery is low, pressing any of the following buttons will result in all of them flashing to indicate a low battery: Lock, Unlock, Panic, Start.

Multiple-Users:

Available to allow multiple users to a single vehicle.

For more information about *Panic Alert*, or to locate an authorized LoadTrak dealer near you, visit www.loadtrak.com or call **1-866-LoadTrk** (1-866-562-3875).